

## **Claims**

1. A safety device for a collar for a pet comprising a central member, a first lateral member for pivotal and releasable engagement with the central member and a second lateral member for pivotal and releasable engagement with the central member.
2. The safety device according to claim 1 wherein the central member is a female member while the lateral members are male members.
3. The safety device according to claim 2 wherein the female member includes a first recess defined in an end and a second recess defined in an opposite, and the first male member includes a cylinder that can be forced into the first recess, and the second male member includes a cylinder that can be forced into the second recess.
4. The safety device according to claim 3 wherein the first recess includes a reduced opening so as to keep the cylinder of the first male member therein.
5. The safety device according to claim 3 wherein the second recess includes a reduced opening so as to keep the cylinder of the second male member therein.
6. The safety device according to claim 3 wherein the first male member includes a bar located opposite to the cylinder thereof to be wound by means of an end of the collar.
7. The safety device according to claim 3 wherein the second male member includes a bar located opposite to the cylinder thereof to be wound by means of an end of the collar.
8. The safety device according to claim 1 wherein the central member is a male member while the lateral members are female members.

1 9. The safety device according to claim 8 wherein the male member  
2 includes a first cylinder formed at an end and a second cylinder  
3 formed at an opposite end, and the first female member defines a  
4 recess into which the first cylinder can be forced, and the second  
5 female member defines a recess into which the second cylinder can be  
6 forced.

7 10. The safety device according to claim 9 wherein the first female  
8 member includes a bar located opposite to the cylinder thereof to be  
9 wound by means of an end of the collar.

10 11. The safety device according to claim 9 wherein the second female  
11 member includes a bar located opposite to the cylinder thereof to be  
12 wound by means of an end of the collar.

13 12. The safety device according to claim 1 wherein the central member  
14 includes a cavity defined in a side for receiving a nametag.

15

16